

# Steam Sterilization “What we need to know to comply with EN285-A Case Study”

PDA Southern California Chapter

4th Annual Full Day Aseptic Processing & Sterilization Symposium

November 7th , 2019

Irvine, California



Connecting People, Science and Regulation®



Connecting People, Science and Regulation®

CONNECTING  
PEOPLE  
SCIENCE AND  
REGULATION®



Connecting People, Science and Regulation®

**Mehron Mirian**  
**VTI Life Science Inc.**

**Office: 800-930-9222**

**Email: [mehron.mirian@validation.org](mailto:mehron.mirian@validation.org)**





## Predicate:

Steam sterilization is considered one of the method to ensure sterility. Steam Sterilization can be used for solutions and dry goods. This case study specifies the minimum documentation required to comply with EN 285. It must be recognized that the control of good manufacturing practices remain of utmost importance.



Connecting People, Science and Regulation®

## Some questions (please chime in):

- This is a case study? What does this mean?
- Why do we have to comply with EN285?
- What document do we capture the requirements?
- What is the focus of this study? In-Process Materials specifically Solids



Connecting People, Science and Regulation®

# Presentation Overview:

- Definitions
- Gap Analysis
- Recommended Tests
- IOPQ




## Definition:

- What does Steam sterilization mean? Steam Sterilization process uses water in its liquid and vaporous state to penetrate as steam.
- Distribution of moisture and temperature throughout the sterilization load is done by comparison of measurement results with cycle parameters shown by validation.
- What does sterilization process mean? Series of operations needed to achieve specified requirements for sterility.



## Definition:

- What does “Sterile” mean in Steam Sterilization? A combination of minimum process parameters to produce substantial overkill
- What is included in Sterilization process? Includes pre-treatment, exposure and post treatment. Sterilization process does not include any cleaning, disinfection or packing operation that precede sterilization.

**Key**

- |       |  |       |  |
|-------|--|-------|--|
| 1     | start of the operating cycle                   | $t_4$ | time at the end of the plateau period  |
| $t_1$ | time at the start of the first steam injection | $t_5$ | time at the start of the drying period |
| $t_2$ | time at the start of the second vacuum pulse   | $t_6$ | time at the end of the drying period   |
| $t_3$ | time at the start of the plateau period        | 2     | end of the operating cycle             |

**Figure 4 — Diagram of specimen operation cycle given as an example only**





Connecting People, Science and Regulation®

## Definition:

- What can effect the reproducibility of sterilization process?
  - Deviation of Cycle Parameters
  - Air retention in the load, Air Leak and Non-Condensable
  - Steam Overheat
  - Load orientation



## Definition:

- EN 285:15:

- There are 25 sections plus 7 annexes
- EN 285 specifies test procedure and criteria to confirm whether sterilizer is **safe** and **deliver** operating cycle and load configuration for sterilizing.
- Steam Sterilizers-Large Sterilizers should follow European Standard.
- EN 285:15 supersedes BS EN 285:2006.



Connecting People, Science and Regulation®

## Definition:

- EN 285:15:

- Approved by CEN

- CEN is the European Committee for Standardization and it brings together the National Standardization Bodies of 34 European countries.



Connecting People, Science and Regulation®

## Definition:

- **Measuring chain:** Series of elements of a measuring instrument or measuring system which constitute the path of the measurement signal from the input to the output.
- **Risk Assessment:** Overall process comprising a risk analysis and risk evaluation
- **Risk Control:** Process through which decisions are reached and protective measures are implemented for reducing risk to, or maintaining risks within, specified levels.



Connecting People, Science and Regulation®

## Definition:

- **Software Validation:** confirmation, through the provision of objective evidence, that the requirements for a specific intended use or application have been fulfilled. This means data integrity.





Connecting People, Science and Regulation®

# Gap Analysis

| Section Name                            | Section #          | Requirement   |
|---|--------------------|---|
| Introduction                            | Introduction       | An Air Detector is optional if there are other methods in place   |
|   | 4.1                | The chamber is at least 60L   |
|   | 4.2                | The materials are appropriate for contact with steam  |
| Dimension, Material and Pressure Vessel | 4.3.1.3            | The cycle will not start if the door is open  |
|   | 4.3.1.5            | The door cannot be opened during a cycle  |
|   | 4.3.2.2            | The unloading side door cannot be opened until "cycle complete" is indicated  |
|   | 4.3.2.4            | The start controller is on the loading side   |
|   | Piping and fitting | 5.1.2   |
| 5.1.3                                   |                    | Pipework for steam and water at temps greater than 60C shall be insulated (except where it would interfere with operation); cold pipework should be insulated as well to prevent condensate |
| Measuring Chain and Recording           | 6.4.2              | At least two independent temp measurement chains such that failure of an element in one chain will not cause error or failure in the second chain   |
|   | 6.4.2.c            | Measurement error does not exceed 1% over 50 to 150C  |
|   | 6.4.4              | At least two independent pressure measurement chains such that failure of an element in one chain will not cause error or failure in the second chain                                       |
|   | 6.4.4.g            | Have a measurement error compensation that a measurement error caused by the ambient temp does not exceed 0.04K/K over the scale range 0KPa to 400KPa.                                      |
|   | 6.5.1.1            | The system shall be designed to ensure integrity of raw data stored in sterilizer   |
|   | 6.5.2.3            | Printed and stored records shall be retrievable and readable when stored for a period of not less than 11 years; national regulations can apply   |



Connecting People, Science and Regulation®

# Gap Analysis

| Section Name                | Section #           | Requirement  |
|-----------------------------|---------------------|--|
| Control System              | 7.1.6               | Any controlled time deviation shall not exceed 1% of the specified value   |
|                             | 7.1.14              | These is an automatic cycle for a leak test which displays the rate of pressure rise in kPa/min;   |
|                             | 7.2.7               | If an air detector is installed, the system includes the ability to display measurements and adjust settings   |
|                             | 7.3.1               | The software classification is established as part of a risk assessment.   |
|                             | 7.3.2               | Software parts related to safety of patients, users, or any other persons shall be verified and validated.   |
| Temperature Characteristics | 8.2.1.2.1/8.2.1.3.1 | In small and full load, the equilibration time shall not exceed 15s for stzts up to 800L usable space and 30s for larger stzts chamber   |
|                             | 8.2.1.2.4/8.2.1.3.4 | The holding time shall not be less that 15 mins and 3 min for stz temps of 121C and 134C respectively  |
| Risk Control                | 11.2.1              | Risk assessment and risk control for sterilizer design and software should be performed following the method and requirements in ISO 14971   |
|                             | 11.2.2              | Risk analysis should address the specific sterilizer design and features. Measures taken for risk reduction shall consider aspects as user knowledge, experience, training, ergonomics, and usability                                |
| Drains                      | 13.8                | The sterilizer shall be designed to operate with a drainage system resistant to water at 100C and be capable of passing the maximum flow rate of water, air and condensed steam (traps or air breaks added per national regulations) |





Connecting People, Science and Regulation®

# Gap Analysis

| Section Name       | Section # | Requirement  |
|--------------------|-----------|--|
| Steam Quality Test | 21.1      | Non-Condensable: the saturated steam containing up to 3.5 ml non-condensable gases collected from 100ml condensate. Repeat the test 3 times.   |
|                    | 21.2      | Dryness: the saturated steam with the dryness value not less than 0.95 where the dryness value denotes the mass of gas fraction in the mass of saturated steam. Basically, excessive moisture cause damp loads and too little moisture makes ultra superheat. Repeat the test 3 times. |
|                    | 21.3      | Superheat: When the steam expands to atmospheric pressure the superheat shall not exceed 25K. Repeat the test 3 times.   |
|                    | 21.4      | Contaminants: Levels are in the presentation   |

# Gap Analysis

**Table 4 — Suggested maximum values of contaminants in condensate from steam supply to the sterilizer chamber**

| Determinant   | Condensate                        |
|---|-----------------------------------|
| Silicate  | ≤ 0,1 mg/l                        |
| Iron  | ≤ 0,1 mg/l                        |
| Cadmium <sup>c</sup>  | ≤ 0,005 mg/l                      |
| Lead <sup>c</sup>   | ≤ 0,05 mg/l                       |
| Rest of heavy metals except iron, cadmium, lead <sup>b</sup>  | ≤ 0,1 mg/l                        |
| Chloride  | ≤ 0,1 mg/l                        |
| Phosphate   | ≤ 0,1 mg/l                        |
| Conductivity (at 20 °C) <sup>a</sup>  | ≤ 4,3 μS/cm                       |
| pH (20 °C) value  | 5 to 7                            |
| Appearance  | Colourless clean without sediment |
| Hardness (Σ Ions of alkaline earth)   | ≤ 0,02 mmol/l                     |
| <p><sup>a</sup> See European Pharmacopeia.</p> <p><sup>b</sup> If the condensate meets the requirements on conductivity, it is not necessary to perform heavy metal tests.</p> <p><sup>c</sup> The limiting values meet the requirements for potable water.</p> |                                   |

# Recommended Tests

Table 5 — Recommended test programme

| Test   | Requirement according to | Test method according to | Type test (see Annex E) | Works test |
|--|--------------------------|--------------------------|-------------------------|------------|
| Thermometric tests                                       |                          |                          |                         |            |
| – Small load   | 8.2.1.2                  | 16.1                     | X                       |            |
| – Full load  | 8.2.1.3                  | 16.2                     | X                       |            |
| Air removal and steam penetration                        |                          |                          |                         |            |
| – Bowie and Dick test                                    | 8.2.2                    | 17                       | X                       | X          |
| – Air leakage  | 8.2.3                    | 18                       | X                       | X          |
| – Air detector, small load <sup>a</sup>                  | 8.2.4.2                  | 19.2                     | X                       | X          |
| – Air detector, full load <sup>a</sup>                   | 8.2.4.3                  | 19.3                     | X                       |            |
| – Air detector function <sup>a</sup>                     | 8.2.4.4                  | 19.4                     | X                       | X          |
| – Hollow load test                                       | 8.2.5                    | 15                       | X                       |            |
| Load dryness tests                                       |                          |                          |                         |            |
| – Small load, textiles                                   | 8.3.1                    | 20.1                     | X                       |            |
| – Full load, textiles                                    | 8.3.2                    | 20.2                     | X                       |            |
| – Metal  | 8.3.3                    | 20.3                     | X                       |            |
| Sound power  | 9.1                      | 9.1                      | X                       |            |
| Rate of pressure change                                  | 10                       | 22                       | X                       |            |
| Steam quality tests                                      |                          |                          |                         |            |
| – Non-condensable gases                                  | 13.3.1                   | 21.1                     | X                       |            |
| – Dryness value  | 13.3.2                   | 21.2                     | X                       |            |
| – Superheat  | 13.3.3                   | 21.3                     | X                       |            |
| X = denote a recommended test                            |                          |                          |                         |            |
| <sup>a</sup> If an air detector is fitted (see 8.2.4.1). |                          |                          |                         |            |



Connecting People, Science and Regulation®

# Recommended Tests

Table D.1 — Suggested tests

| Test  | Requirements according to clause | Test according to clause | Installation Qualification | Operational Qualification |
|---|----------------------------------|--------------------------|----------------------------|---------------------------|
| Safety Tests and checks   | 11                               |                          | XX                         | —                         |
| Steam quality tests   |                                  |                          |                            |                           |
| - Non-condensable gases   | 13.3.1                           | 21.1                     | X                          | X                         |
| - Dryness value   | 13.3.2                           | 21.2                     | X                          | X                         |
| - Superheat   | 13.3.3                           | 21.3                     | X                          | X                         |
| - Contaminants  | Table 4                          | a                        | X                          | X                         |
| Thermometric tests  |                                  |                          |                            |                           |
| - Small load  | 8.2.1.2                          | 16.1                     | —                          | XX                        |
| - Full load   | 8.2.1.3                          | 16.2                     | —                          | XX                        |
| Hollow load test <sup>b</sup>   | 8.2.5                            | 15                       | —                          | XX                        |
| Bowie and Dick test   | 8.2.2                            | 17                       | —                          | XX                        |
| Rate of pressure rise caused by air leakage   | 8.2.3                            | 18                       | —                          | XX                        |
| Air detector <sup>c</sup>   |                                  |                          |                            |                           |
| - Small load  | 8.2.4.2                          | 19.2                     | —                          | XX                        |
| - Full load   | 8.2.4.3                          | 19.3                     | —                          | XX                        |
| - Function  | 8.2.4.4                          | 19.4                     | —                          | XX                        |
| Load dryness tests  |                                  |                          |                            |                           |
| - Small load, textiles  | 8.3.1                            | 20.1                     | —                          | X                         |
| - Full load, textiles   | 8.3.2                            | 20.2                     | —                          | XX                        |
| - Metal   | 8.3.3                            | 20.3                     | —                          | X                         |
| Rate of pressure change   | 10                               | 22                       | —                          | X                         |
| XX tests which are suggested<br>X tests which can be considered<br>— tests which need not be performed during IQ and/or OQ<br>a Compliance tested in accordance with acknowledged analytical methods.<br>b This test is not intended to be used as a routine daily test.<br>c If an air detector is fitted (see 8.2.4.1). |                                  |                          |                            |                           |



## IOPQ:

- IQ: Typical verification of supporting documentation and filed verification
- OQ: Typical testing of control system and Empty chamber mapping
- PQ for dry goods using one cycle:
  - Engineering study:
    - Consulted with users (Manufacturing) and a list of all items were identified



Connecting People, Science and Regulation®

## IOPQ:

- Engineering study:
  - Items were double bagged in autoclave pouches
  - Wireless temperature sensors we placed into each of the items
  - One conservative cycle by consideration of high loading capacity was selected. The cycle had five (5) pre-pulses and one (1) post-pulse (needed for drying).



Connecting People, Science and Regulation®

## IOPQ:

- Engineering study:
  - After completion of all runs, a comparison of accumulated lethality (F0) during the hold time was performed.
  - Items with lower F0 was considered “worst-case”.
  - Total of eight (8) items were identified



Connecting People, Science and Regulation®

# IOPQ:

- PQ:

- Engineering study determined the load and the cycle
- Challenged sterilizer in minimum and maximum load configuration.
- Based on the number of racks in two shelves (4) , and number of items (8), a total of 32 items were distributed as maximum. One item was used as minimum.
- Used Biological Indicators





Connecting People, Science and Regulation®

IOPQ:

• PQ:

- Following two bullets from section 8.2.1 “Temperature characterization” were critical and used as acceptance criteria:

- During the sterilization phase, temperature sensors shall not exceed the temperature measured at drain sensor (reference point) by more than 5°C for the first 60 second and 2°C for the remaining period.



Connecting People, Science and Regulation®

IOPQ:

• PQ:

–Throughout the sterilization phase, temperature measured at drain sensor, all temperature sensors and the theoretical temperature of the saturated steam determined from the pressure sensor shall be within the sterilizer temperature band and not differ from one another by more than 2°C.



Connecting People, Science and Regulation®

IOPQ:

• PQ:

- The other criteria were routine PQ acceptance criteria such calibration, F0, temperature within sterilization band,....



Connecting People, Science and Regulation®

A large, light gray, stylized globe graphic is positioned on the left side of the slide. It consists of a semi-circle at the top with a grid of lines representing latitude and longitude, and a larger, more complex grid pattern below it. The text 'Thank You' is centered to the right of the globe.

# Thank You